

EAGLE

دستگاه شخصی سازی کارت مدل EAGLE

دستگاه شخصی سازی مدل EAGLE با طراحی منحصر به فرد از نظر ابعاد و وزن کاهش قابل ملاحظه ای نسبت به دستگاه مدل صنعتی پیدا کرده است. این دستگاه دارای مخزن ورودی کارت می باشد به نحوی که به صورت کاملا اتوماتیک کارت در دستگاه وارد می شود و سپس اطلاعات بر روی چیپ (تماسی یا غیرتماسی) یا نوار مغنت حکاکی اطلاعات اعم از متن یا تصاویر با بالاترین وضوح ممکن صورت می پذیرد. این مدل ضمن کاربرد در مجموعه های با محدودیت مکانی و برای شخصی سازی برای حجم های متوسط کارت ها مناسب می باشد و به دلیل نوع منبع لیزر جهت حکاکی تصاویر و کارت های شناسایی بسیار ایده آل می باشد.

150 cards output capacity	100 to up cards Input capacity	300 cph speed	*1200 Dpi Resolution	1 or 2 sided Print mode	PC/PVC/PET/METAL Card type	MS/IC/RE Encoding options	LAN
------------------------------	-----------------------------------	------------------	-------------------------	----------------------------	-------------------------------	------------------------------	-----





دستگاه شخصی سازی کارت مدل EAGLE

Technical Specification of Laser personalization eagle

Laser Engine	
Type of Laser	Diode
Laser Power	3 w
Laser Wavelength	IR-1064nm.
Resolution	1200dpi
Engraving Mode	Single & Dual-Sided Laser Engraver
laser life time	20.000h
Throughputs	
Card Feeding	One Feeder Magazine
Maximum Speed	350 cph (Base on data size for encoding)
Repeated positioning	± 500 micron
Card Input Feeder	Automatic 150 - 100 cards
Card	
Card Thickness	760 ± 80 mic (ISO7816)
Card Size	ID1 (53/98 x 85/60mm)
Card Type	PVC, Laserable PVC, PC, PETG, ABS
System Properties	
Image Area	86×54 mm
Minimum Character	6 pt, 2 pt (Laserable subs.)
Cooling Methode	By Air
Control Panel	Start Button
Operation System	Windows 10
Communication	USB3
Flipper turner	Yes
Vision QC Unit	Optional
Provision for External Air Vacuum Filter	Optional
Software	Standalone/ Web API Services/SDK
Contact Module	ISO 7816 (Read & Write)
Contact Module	ISO 14443 (Type A/B), Mifare, DESFire ,iCLASS, ISO 18092 (NFC)
Magnetic module	ISO 7810, ISO 7811, ISO 7812, ISO 7813, ISO 8583, ISO 4909 (Read & Write track 1 ,2 ,3 HiCo)
Machine Weight	35 kg (Approx.)
Dimensions	59×110×158 (cm)
Power Consumptions	1,400-2,200 W
Security	
Physical lock	At Input Feeder
Laser Safety	Class-IV inside, Class-I outside
Environmental Condition	
Room Temperature	15 - 25 °C
Room Humidity	%20 ~ %50
Room Condition	ISO 9
Power Supply	Single Phase 220 VAC (It's suggested that Use Stabilizer or UPS)
Earthing System	ISO 60364